



Fonrita
方瑞達電子


MOLDING POWER INDUCTORS

一體成型電感


Type: CDMC1050




Dimensions外形尺寸 (mm)



Recommended Land Pattern (mm)



PRODUCT IDENTIFICATION/產品標識



1. Product symbol/產品類型 : CDMC (shield/屏蔽)
2. Body length/產品長度 : mm
3. Body height/產品高度 : mm
4. Inductance/感量 : μH
5. Tolerance/公差 : M $\pm 20\%$, N $\pm 30\%$
6. RoHs Compliant(SGS Certified)

本產品滿足環境保護要求(有害物質限用)



FEATURES:

- Quantity/reel:500PCS.
- Square 11.0mm type(11.5mm Max),Height 5.0mm Max.
- Carbonyl Powder.
- High current,low DCR,high efficiency.
- Widely use in DC-DC converter/Notebook/CPU/
Portable communications equipment/Camcorders/HDTV/car audio .

特長:

- 數量/卷:500PCS.
- 方形11.0mm(11.5mm Max),高度5.0mm Max.
- 材質羰基粉.
- 大電流, 低直流電阻, 高效率.
- 廣泛應用於升降壓轉換器/筆記本電腦/電腦主板/
便攜式通訊設備/攝像機/高清電視/汽車音響.

ELECTRICAL CHARACTERISTICS/電氣特性

Part NO. 品名	Inductance 電感量(μH)	Tolerance 公差(%)	D.C.R. 直流電阻		I sat(Typ.) 飽和電流(A)	I rms(Typ.) 溫升電流(A)
			Typ(m Ω)	Max(m Ω)		
CDMC1050-R22	0.22	M	0.45	0.50	70.0	45.0
CDMC1050-R56	0.56	M	1.30	1.50	43.0	26.5
CDMC1050-1R0	1.0	M	2.80	3.50	30.0	22.0
CDMC1050-1R5	1.5	M	3.50	4.10	27.0	19.0
CDMC1050-2R2	2.2	M	5.40	6.00	24.0	16.0
CDMC1050-3R3	3.3	M	9.0	10.4	22.0	14.0
CDMC1050-4R7	4.7	M	10.0	12.5	19.0	13.0
CDMC1050-5R6	5.6	M	14.0	16.8	16.0	10.0
CDMC1050-6R8	6.8	M	16.5	21.0	15.0	9.50
CDMC1050-8R2	8.2	M	18.5	24.0	14.5	9.00
CDMC1050-100	10	M	25.0	29.0	13.5	8.00
CDMC1050-150	15	M	37.0	45.0	9.50	5.50
CDMC1050-220	22	M	50.0	60.0	9.00	5.00
CDMC1050-330	33	M	80.0	92.0	7.50	4.30
CDMC1050-470	47	M	125.0	145.0	6.50	3.80
CDMC1050-680	68	M	176.0	205.0	4.00	2.50
CDMC1050-101	100	M	315.0	380.0	3.00	2.00

Inductance Range/電感範圍:0.22~100 μH

Operating Temperature/工作溫度: -40°C ~ +125°C

Storage Temperature/儲存溫度: -40°C ~ +125°C

(1) Test frequency :100KHz/1.0V;


(2) The maximum allowable current is a DC current which causes initial inductance to decrease by 30%,or temperature to rise by 40°C, whichever is smaller(At ambient reference temperature:25°C).

(1) 電感測試頻率:100KHz/1.0V;


(2) 最大容許電流定義:電感下降30%或溫度上升40°C時,取其小值作為最大容許電流(周圍環境溫度25°C).



Electrical Schematic/原理圖



Recommended Temperature Conditions of Air Reflow Soldering/推薦回流焊溫度條件



In addition to the standards versions shown here, custom inductors are also available to meet your exact requirements.

除了這裡顯示的標準品之外,可根據客戶要求進行設計.

www.fonrita.com