



Fonrita
方瑞達電子


MOLDING POWER INDUCTORS

一體成型電感


Type: CDMC1260




Dimensions外形尺寸(mm)



Recommended Land Pattern(mm)



PRODUCT IDENTIFICATION/產品標識



1. Product symbol/產品類型 : CDMC (shield/屏蔽)
2. Body length/產品長度 : mm
3. Body height/產品高度 : mm
4. Inductance/感量 : μH
5. Tolerance/公差 : M $\pm 20\%$, N $\pm 30\%$
6. RoHs Compliant(SGS Certified)

本產品滿足環境保護要求(有害物質限用)



FEATURES:

- Quantity/reel:500PCS.
- Square 13.5mm type(14.0mm Max),Height 6.0mm Max.
- Carbonyl Powder.
- High current,low DCR,high efficiency.
- Widely use in DC-DC converter/Notebook/CPU/
Portable communications equipment/Camcorders/HDTV/car audio .

特長:

- 數量/卷:500PCS.
- 方形13.5mm(14.0mm Max),高度6mm Max.
- 材質羰基粉.
- 大電流, 低直流電阻, 高效率.
- 廣泛應用於升降壓轉換器/筆記本電腦/電腦主板/
便攜式通訊設備/攝像機/高清電視/汽車音響.

ELECTRICAL CHARACTERISTICS/電氣特性

Part NO. 品名	Inductance 電感量(μH)	Tolerance 公差(%)	D.C.R. 直流電阻		I sat(Typ.) 飽和電流(A)	I rms(Typ.) 溫升電流(A)
			Typ(m Ω)	Max(m Ω)		
CDMC1260-R22	0.22	N	0.48	0.65	120.0	55.0
CDMC1260-R36	0.36	M	0.72	0.90	80.0	42.0
CDMC1260-R47	0.47	M	0.92	1.30	64.0	38.0
CDMC1260-R56	0.56	M	1.15	1.50	60.0	35.0
CDMC1260-R68	0.68	M	1.33	1.70	57.0	33.0
CDMC1260-R82	0.82	M	1.50	1.90	55.0	31.0
CDMC1260-1R0	1.0	M	1.80	2.40	53.0	29.0
CDMC1260-1R5	1.5	M	2.70	3.20	50.0	26.0
CDMC1260-2R2	2.2	M	4.00	4.70	43.0	21.0
CDMC1260-3R3	3.3	M	5.80	7.10	35.0	17.0
CDMC1260-4R7	4.7	M	9.50	11.5	30.0	16.0
CDMC1260-5R6	5.6	M	10.8	12.6	28.0	15.5
CDMC1260-6R8	6.8	M	12.0	13.8	25.0	15.0
CDMC1260-8R2	8.2	M	13.6	16.0	23.0	11.0
CDMC1260-100	10	M	18.0	20.7	21.0	11.0
CDMC1260-150	15	M	25.0	29.0	16.0	9.0
CDMC1260-180	18	M	30.0	35.0	15.0	8.5
CDMC1260-220	22	M	34.0	39.5	14.0	8.0
CDMC1260-330	33	M	65.0	75.0	12.0	6.0
CDMC1260-470	47	M	80.0	90.0	11.0	5.5
CDMC1260-680	68	M	120.0	140.0	9.0	5.0
CDMC1260-820	82	M	138.0	161.0	5.5	4.5
CDMC1260-101	100	M	180.0	200.0	5.0	4.0

Inductance Range/電感範圍:0.22~100 μH

Operating Temperature/工作溫度:-40°C ~ +125°C

Storage Temperature/儲存溫度:-40°C ~ +125°C

(1) Test frequency :100KHz/1.0V;


(2) The maximum allowable current is a DC current which causes initial inductance to decrease by 30%,or temperature to rise by 40°C, whichever is smaller(At ambient reference temperature:25°C).

(1) 電感測試頻率:100KHz/1.0V;


(2) 最大容許電流定義:電感下降30%或溫度上升40°C時,取其小值作為最大容許電流(周圍環境溫度25°C).



Electrical Schematic/原理圖



Recommended Temperature Conditions of Air Reflow Soldering/推薦回流焊溫度條件



In addition to the standards versions shown here, custom inductors are also available to meet your exact requirements.

除了這裡顯示的標準品之外,可根據客戶要求進行設計.

www.fonrita.com