





Type: FDRH5D18




Dimensions外形尺寸(mm)



Recommended Land Pattern(mm)



PRODUCT IDENTIFICATION/產品標識



1. Product symbol/產品類型 : FDRH (shield/屏蔽)
2. Body length/產品長度 : mm
3. Body height/產品高度 : mm
4. Inductance/感量 : μH
5. Tolerance/公差 : M $\pm 20\%$, N $\pm 30\%$
6. RoHS Compliant(SGS Certified)

本產品滿足環境保護要求(有害物質限用)



FEATURES:

- Quantity/reel:2000PCS.
- Square 5.7mm type(6.0mm Max),Height 2.0mm Max.
- Magnetically shielded construction.
- Suitable for reflow soldering.
- Widely use in DC-DC converter/LCD TV/Notebook/PDA/Digital camera/Portable CDR-W etc.

特長:

- 數量/卷:2000PCS.
- 方形5.7mm(6.0mm Max),高度2.0mm Max.
- 閉磁路構造設計.
- 適用於回流焊SMT工藝.
- 廣泛應用於升降壓轉換器/液晶顯示器/筆記本電腦/個人掌上記事本/數碼相機/便攜式光碟機等.

ELECTRICAL CHARACTERISTICS/電氣特性

Part NO. 品名	Inductance 電感量(μH)	Tolerance 公差(%)	DC Resistance 直流電阻Max(Ω)	Rated Current 額定電流Max(A)
FDRH5D18-4R1	4.1	N	0.057	1.95
FDRH5D18-5R4	5.4	N	0.076	1.60
FDRH5D18-6R2	6.2	N	0.096	1.40
FDRH5D18-8R9	8.9	N	0.116	1.25
FDRH5D18-100	10	M	0.124	1.20
FDRH5D18-120	12	M	0.153	1.10
FDRH5D18-150	15	M	0.196	0.97
FDRH5D18-180	18	M	0.210	0.85
FDRH5D18-220	22	M	0.290	0.80
FDRH5D18-270	27	M	0.330	0.75
FDRH5D18-330	33	M	0.386	0.65
FDRH5D18-390	39	M	0.520	0.57
FDRH5D18-470	47	M	0.595	0.54
FDRH5D18-560	56	M	0.665	0.50
FDRH5D18-680	68	M	0.840	0.43
FDRH5D18-820	82	M	0.978	0.41
FDRH5D18-101	100	M	1.200	0.36
FDRH5D18-121	120	M	1.500	0.33
FDRH5D18-151	150	M	1.710	0.31
FDRH5D18-181	180	M	2.240	0.28
FDRH5D18-221	220	M	2.440	0.23
FDRH5D18-271	270	M	3.380	0.21
FDRH5D18-331	330	M	4.340	0.18

Inductance Range/電感範圍:4.1~330 μH

Operating Temperature/工作溫度: $-40^{\circ}\text{C} \sim +125^{\circ}\text{C}$

Storage Temperature/儲存溫度: $-40^{\circ}\text{C} \sim +125^{\circ}\text{C}$

(1) Test frequency :100KHz/0.1V;

(2) The maximum allowable current is a DC current which causes initial inductance to decrease by 35%, or temperature to rise by 40°C , whichever is smaller (At ambient reference temperature: 25°C).

(1) 電感測試頻率:100KHz/0.1V;


(2) 最大容許電流定義:電感下降35%或溫度上升 40°C 時,取其小值作為最大容許電流(周圍環境溫度 25°C).



Electrical Schematic/原理圖



Recommended Temperature Conditions of Air Reflow Soldering/推薦回流焊溫度條件



In addition to the standards versions shown here, custom inductors are also available to meet your exact requirements.

除了這裡顯示的標準品之外,可根據客戶要求進行設計。

www.fonrita.com