







Type: FSLF1265




Dimensions外形尺寸(mm)



Recommended Land Pattern(mm)



PRODUCT IDENTIFICATION/產品標識



1. Product symbol/產品類型 : FSLF (Shielded/屏蔽)
2. Body length/產品長度 : mm
3. Body height/產品高度 : mm
4. Inductance/感量 : μH
5. Tolerance/公差 : M $\pm 20\%$, N $\pm 30\%$
6. RoHS Compliant(SGS Certified)

本產品滿足環境保護要求(有害物質限用)



FEATURES:

- Quantity/reel:500PCS.
- Square 12.8mm Max,Height 6.8mm Max.
- Magnetically shielded construction.
- Suitable for reflow soldering.
- Widely use in DC-DC converter/LCD TV/Notebook/PDA/Digital camera/Portable CDR-W etc.

特長:

- 數量/卷:500PCS.
- 方形12.8mm Max,高度6.8mm Max.
- 閉磁路構造設計.
- 適用於回流焊SMT工藝.
- 廣泛應用於升降壓轉換器/液晶電視/筆記本電腦/個人掌上記事本/數碼相機/便攜式光碟機等.

ELECTRICAL CHARACTERISTICS/電氣特性

Part NO. 品名	Inductance 電感量(μH)	Tolerance 公差(%)	DC Resistance 直流電阻Max(Ω)	Rated Current 額定電流Max(A)
FSLF1265-2R0	2.0	N	0.015	10.00
FSLF1265-4R2	4.2	N	0.018	7.30
FSLF1265-7R0	7.0	N	0.022	5.70
FSLF1265-100	10	M	0.025	5.00
FSLF1265-150	15	M	0.029	4.20
FSLF1265-220	22	M	0.038	3.50
FSLF1265-330	33	M	0.049	2.80
FSLF1265-470	47	M	0.070	2.40
FSLF1265-680	68	M	0.095	2.00
FSLF1265-101	100	M	0.148	1.60
FSLF1265-221	220	M	0.328	1.00

Inductance Range/電感範圍:2.0~220 μH

Operating Temperature/工作溫度: $-40^{\circ}\text{C} \sim +125^{\circ}\text{C}$

Storage Temperature/儲存溫度: $-40^{\circ}\text{C} \sim +125^{\circ}\text{C}$

(1) Test frequency:1KHz/0.25V;

(2) The maximum allowable current is a DC current which causes initial inductance to decrease by 10%, or temperature to rise by 40°C , whichever is smaller (At ambient reference temperature: 25°C).

(1) 電感測試頻率:1KHz/0.25V;


(2) 最大容許電流定義:電感下降10%或溫度上升 40°C 時,取其小值作為最大容許電流(周圍環境溫度 25°C).



Electrical Schematic/原理圖



Recommended Temperature Conditions of Air Reflow Soldering/推薦回流焊溫度條件



In addition to the standards versions shown here, custom inductors are also available to meet your exact requirements.

除了這裡顯示的標準品之外,可根據客戶要求進行設計.

www.fonrita.com